



## **PENNZOIL ULTRA™ EURO L FULL SYNTHETIC MOTOR OIL 5W-30**

### **PRODUCT DESCRIPTION**

PENNZOIL ULTRA™ EURO L FULL SYNTHETIC MOTOR OIL 5W-30 with Hyper Cleansing Technology™, from the maker of the leading motor oil in America, is an advanced proprietary low SAPS synthetic formula designed to exceed the toughest car manufacturer standards for engines with and without exhaust after treatment devices. The lubricant is engineered to keep your engine closer to factory clean, because at Pennzoil we know, a cleaner engine is better protected, more efficient and delivers optimum performance.

### **APPLICATION**

PENNZOIL ULTRA™ EURO L FULL SYNTHETIC MOTOR OIL 5W-30 with Hyper Cleansing Technology™ is suitable for fuel-injected gasoline engines fitted with 'blow-by' recirculation and catalytic converters operating in extreme driving conditions; and also is suitable for turbo-charged and inter-cooled direct injection high performance diesel engines fitted with 'blow-by' recirculation and exhaust gas recirculation without particulate filters. PENNZOIL ULTRA™ EURO L FULL SYNTHETIC MOTOR OIL 5W-30 with Hyper Cleansing Technology™ is compatible with all engine sealing materials, other synthetic oils and all conventional oils.

### **FEATURES**

- Hyper Cleansing Technology™
- Low SAPS (Sulfated Ash, Phosphorus & Sulfur)
- Low Volatility Oil

### **BENEFITS**

- Seeks out and dissolves contaminants safely into the oil before they form deposits in the engine.
- Helps to prevent the build-up of sludge, damaging deposits, corrosion and engine wear.
- Helps clean-up engines by gently lifting sludge deposits off engine surfaces and dissolving them safely into the oil.
- Provides oil stability and endurance under extreme conditions (heat, load and speed) for protection against viscosity and thermal breakdown.
- Provides proven protection for critical engine parts.
- Helps protect emissions systems.
- Reduces exhaust filter blocking.

### **SPECIFICATIONS & APPROVALS**

- MB 229.51
- VW 504 00 and VW 507 00
- BMW LL-04
- Chrysler MS-10725
- Porsche C30
- Exceeds the requirements of ACEA C2 & C3 (A3/B3/B4)

### **HEALTH & SAFETY**

Guidance on Health and safety is available on the appropriate Material Safety Data Sheet, which can be obtained from your local Pennzoil representative.

### **PROTECT THE ENVIRONMENT**

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.



**TYPICAL PHYSICAL AND CHEMICAL PROPERTIES  
PENNZOIL ULTRA™ EURO L FULL SYNTHETIC MOTOR OIL 5W-30**

TEST	METHOD	TYPICAL RESULTS
<b>Viscosity Grade.</b>		<b>5W-30</b>
ACEA		C2 & C3 (A3/B3/B4)
Gravity, °API	ASTM D-287	34.0
Specific Gravity @ 60°F(15.6°C)	ASTM D-287	0.85
Viscosity		
@ 40°C, cSt	ASTM D-445	67.1
@ 100°C, cSt	ASTM D-445	12.0
Flash Point, °F	ASTM D-93	420
Pour Point, °C	ASTM D-97	-39
CCS Viscosity, cP (°C)	ASTM D-5293	6600 max (-30)
HT/HS Viscosity, cP	ASTM D-4683	3.68
Noack Volatility, %	ASTM D-5800	11

These characteristics are typical. While future production will conform to Pennzoil's specifications, variations in these characteristics may occur. The information contained herein is subject to change without notification.