



PENNZOIL ULTRA™ EURO 5W-40 FULL SYNTHETIC MOTOR OIL

PRODUCT DESCRIPTION

PENNZOIL ULTRA™ EURO 5W-40 FULL SYNTHETIC MOTOR OIL with Hyper Cleansing Technology™, from the maker of the leading motor oil in America, is an advanced proprietary synthetic formula designed to exceed the toughest car manufacturer standards and engineered to keep your engine closer to factory clean. Because at Pennzoil we know, a cleaner engine is better protected, more efficient and delivers optimum performance.

APPLICATION

PENNZOIL ULTRA™ EURO 5W-40 FULL SYNTHETIC MOTOR OIL with Hyper Cleansing Technology™ is suitable for fuel-injected gasoline engines fitted with 'blow-by' recirculation and catalytic converters operating in extreme driving conditions; and also is suitable for turbo-charged and inter-cooled direct injection high performance diesel engines fitted with 'blow-by' recirculation and exhaust gas recirculation without particulate filters. PENNZOIL ULTRA™ EURO 5W-40 FULL SYNTHETIC MOTOR OIL with Hyper Cleansing Technology™ also is compatible with all engine sealing materials, other synthetic oils and all conventional oils and is suitable for all cars, SUV's, light vans and trucks, gasoline and turbocharged engines under all driving conditions.

FEATURES

- Hyper Cleansing Technology™
- Low Volatility Oil

BENEFITS

- Seeks out and dissolves contaminants safely into the oil before they form deposits in the engine.
- Helps to prevent the build-up of sludge, damaging deposits, corrosion and engine wear.
- Helps clean-up engines by gently lifting sludge deposits off engine surfaces and dissolving them safely into the oil.
- Provides oil stability and endurance under extreme conditions (heat, load and speed) for protection against viscosity and thermal breakdown.
- Provides proven protection for critical engine parts.
- Helps protect emissions systems.

SPECIFICATIONS & APPROVALS

- Ferrari – Exclusive to Pennzoil Ultra™ in the USA
- Porsche A40
- MB 229.5 and MB 229.3
- VW 502 00 and VW 505 00
- VW/Audi 503 01
- Fiat 9.5535 Z2
- BMW LL-01
- Chrysler MS-10725
- Exceeds the requirements of ACEA A3/B3/B4
- Exceeds the requirements of API SM/CF and previous categories

HEALTH & SAFETY

Guidance on Health and safety is available on the appropriate Material Safety Data Sheet, which can be obtained from your local Pennzoil representative.

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

March 2010

001D7471



**TYPICAL PHYSICAL AND CHEMICAL PROPERTIES
PENNZOIL ULTRA™ EURO 5W-40 FULL SYNTHETIC MOTOR OIL**

TEST	METHOD	TYPICAL RESULTS
Viscosity Grade.		5W-40
API Service		SM/CF
ACEA		A3/B3/B4-04
Gravity, °API	ASTM D-287	34.0
Specific Gravity @ 60°F(15.6°C)	ASTM D-287	0.85
Viscosity		
@ 40°C, cSt	ASTM D-445	74.4
@ 100°C, cSt	ASTM D-445	13.1
Flash Point, °F	ASTM D-93	420
Pour Point, °C	ASTM D-97	-39
CCS Viscosity, cP (°C)	ASTM D-5293	6600 max (-30)
HT/HS Viscosity, cP	ASTM D-4683	3.68
Noack Volatility, %	ASTM D-5800	11

These characteristics are typical. While future production will conform to Pennzoil® specifications, variations in these characteristics may occur. The information contained herein is subject to change without notification.